

## Product Specification

Colour	Dark Brown
Appearance	Semi Liquid to Stick Grade
Texture	Tacky
Solid Lubricant	PTFE
Base Oil	Synthetic
Dropping Point	None
Worked Penetration @25°C	min 170 in Bulk from min 80 in Stick from
Compatibility	Excellent
Solvent Resistance	Excellent
Operating Temperature	-20 °C to +240°C

## Order Details

### Ordering Size

Ordering Size	Part No.
A Stick – 6.35 × 22.23 (mm) – 90/ Box	S-HT 500-90 A
B Stick – 10.32 × 34.93 (mm) – 48/ Box	S-HT 500-48 B
C Stick – 13.89 × 50.80 (mm) – 24/ Box	S-HT 500-24 C
D Stick – 16.67 × 61.91 (mm) – 24/ Box	S-HT 500-24 D
G Stick – 21.83 × 85.73 (mm) – 24/ Box	S-HT 500-24 G
J Stick – 37.31 × 222.25 (mm) – 4/Box	S-HT 500-4 J
J Stick – 37.31 × 222.25 (mm) – 6/Box	S-HT 500-6 J
J Stick – 37.31 × 222.25 (mm) – 12/Box	S-HT 500-12 J
K Stick – 38.89 × 254.00 (mm) – 4/Box	S-HT 500-4 K
K Stick – 38.89 × 254.00 (mm) – 6/Box	S-HT 500-6 K
K Stick – 38.89 × 254.00 (mm) – 12/Box	S-HT 500-12 K
4.5 Kg Tin	S-HT 500-4.5 Kg
18 Kg Pail	S-HT 500-18 Kg
250 gr. Tube	S-HT 500-250 gr

LAGA HT-500/S ماده آببندی و روانکاری شیرآلات Ball, Plug از نوع سنتتیک میباشد.  
LAGA HT-500/S جهت آببندی شیرهای در حال کار و با نشتی زیاد فرموله شده تا فشار 10000 psi آببندی لازم را فراهم می آورد.  
LAGA HT-500/S برای استفاده در شیرآلات در تماس با گاز طبیعی، میعانات گازی و سایر فرآورده های سبک نفت خام بسیار مناسب بوده و طول عمر بالایی دارد.

LAGA HT-500/S Valve Sealant is formulated from non-toxic, high viscosity synthetic base oil and polymers to assure heavy duty sealing and lubrication in a wide range of general purpose applications where resistance to aliphatic hydrocarbons or aqueous solutions is required. LAGA HT-500/S is recommended for use in plug and ball valves when maximum sealing power is required.

