

Product Specification

Colour	Light Yellow
Appearance	Semi Liquid to Stick Grade
Texture	Tacky
Base Oil	Synthetic
Dropping Point	None
Worked Penetration @25°C	min 170 in Bulk from min 80 in Stick from
Compatibility	Excellent
Solvent Resistance	Excellent
Operating Temperature	-24 °C to +180°C

Order Details

Ordering Size	Part No.
A Stick – 6.35 × 22.23(mm) – 90/ Box	HRF-1000-90 A
B Stick – 10.32 × 34.93(mm) – 48/ Box	HRF-1000-48 B
C Stick – 13.89 × 50.80(mm) – 24/ Box	HRF-1000-24 C
D Stick – 16.67 × 61.91 (mm)– 24/ Box	HRF-1000-24 D
G Stick – 21.83 × 85.73 (mm)– 24/ Box	HRF-1000-24 G
J Stick – 37.31 × 222.25 (mm) – 4/Box	HRF-1000-4 J
J Stick – 37.31 × 222.25 (mm) – 6/Box	HRF-1000-6 J
J Stick – 37.31 × 222.25 (mm) – 12 /Box	HRF-1000-12 J
K Stick – 38.89 × 254.00 (mm) – 4/Box	HRF-1000-4 K
K Stick – 38.89 × 254.00 (mm) – 6/Box	HRF-1000-6 K
K Stick – 38.89 × 254.00 (mm) – 12 /Box	HRF-1000-12 K
4.5 Kg Tin	HRF-1000-4.5 Kg
18 Kg Pail	HRF-1000-18 Kg
250 gr. Tube	HRF-1000-250 gr

RAGA HRF-1000 ماده روانکاری و آبیندی شیرآلات Ball ، Plug و Gate از نوع سنتتیک می باشد.

RAGA HRF-1000 جهت استفاده در خطوط انتقال حلال های هیدروکربنی مانند بنزین، تولوئن و هر جا که نیاز به مقاومت بالا در برابر هیدروکربن ها باشد به کار برده می شود. RAGA HRF-1000 برای استفاده در شیرآلات خطوط لوله پخش فرآورده های نفتی مناسب بوده و طول عمر بالایی دارد.

RAGA HRF-1000 Valve Sealant and Lubricant is formulated from non-toxic and high viscosity synthetic base oil to assure excellent lubrication and sealing in a wide range of general purpose application where resistance to aliphatic hydrocarbons is required. RAGA HRF-1000 is recommended for Plug, Ball and Gate valves to use in refinery and petrochemical transfer pipelines.

