

Product Specification

Colour	Black
Appearance	Semi Liquid to Stick Grade
Texture	Tacky
Solid Lubricant	Graphite
Base Oil	Synthetic
Dropping Point	None
Worked Penetration @25°C	min 170 in Bulk from min 80 in Stick from
Compatibility	Excellent
Solvent Resistance	Excellent
Operating Temperature	-24 °C to +200°C

Order Details

Ordering Size	Part No.
A Stick – 6.35 × 22.23 (mm) – 90/ Box	HRF-1000P-90 A
B Stick – 10.32 × 34.93 (mm) – 48/ Box	HRF-1000P-48 B
C Stick – 13.89 × 50.80 (mm) – 24/ Box	HRF-1000P-24 C
D Stick – 16.67 × 61.91 (mm) – 24/ Box	HRF-1000P-24 D
G Stick – 21.83 × 85.73 (mm) – 24/ Box	HRF-1000P-24 G
J Stick – 37.31 × 222.25 (mm) – 4/Box	HRF-1000P-4 J
J Stick – 37.31 × 222.25 (mm) – 6/Box	HRF-1000P-6 J
J Stick – 37.31 × 222.25 (mm) – 12/Box	HRF-1000P-12 J
K Stick – 38.89 × 254.00 (mm) – 4/Box	HRF-1000P-4 K
K Stick – 38.89 × 254.00 (mm) – 6/Box	HRF-1000P-6 K
K Stick – 38.89 × 254.00 (mm) – 12/Box	HRF-1000P-12 K
4.5 Kg Tin	HRF-1000P-4.5 Kg
18 Kg Pail	HRF-1000P-18 Kg
250 gr. Tube	HRF-1000P-250 gr

RAGA HRF-1000 Plus ماده روانکاری و آبیندی شیرآلات Gate از نوع سنتتیک می باشد. RAGA HRF-1000 Plus جهت استفاده در شیرآلات سر چاه های نفت و گاز به کار برده میشود.

RAGA HRF-1000 Plus برای استفاده در شیرآلات در تماس با گاز طبیعی، میعانات گازی و سایر فرآورده های سبک نفت خام بسیار مناسب بوده، همچنین مقاومت زیادی در برابر هیدروکربن ها و طول عمر بالایی دارد.

RAGA HRF-1000 Plus Valve Sealant and Lubricant is formulated from non-toxic, high viscosity synthetic base oil and Graphite to assure heavy duty sealing and lubrication in a wide range of general purpose application where resistance to aliphatic hydrocarbons is required.

RAGA HRF-1000 Plus is recommended for Gate valve.

